Application/Control Number: 10/588,657 Page 2

Art Unit: 2166

DETAILED ACTION

Response to Amendments

1. Concerning the examiner's amendment filed 3/20/2009, the amendment was filed without knowledge or indication of applicant's amended claims set filed 3/16/2009. Due to the conflicting status of some of the remaining claims, the applicant's amendments filed 3/16/2009 will not be entered and the following supplementary examiner's amendment will instead be entered. Modifications have been made which are felt to best reflect the combined limitations of both amended claim sets as per the examiner interview of 4/15/2009.

EXAMINER'S AMENDMENT

- 2. An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.
- 3. The application has been amended as follows:

Claims 1-63 (Cancelled)

64. (Previously Presented) A method of storing a data set on a storage device having one or more portions of random data comprising:

Art Unit: 2166

determining using a process dependent upon a user input passphrase, a first storage writing process starting location at a first offset within one of the portions of random data for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within one of the portions of random data for initiating a second storage writing process for storing the data set, said second offset determined using a process that is independent of the process used to generate said first offset;

encrypting the data set;

writing the encrypted data set using the second storage writing process beginning at the second storage writing process starting location in one of the portions of random data; creating the file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location; encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location in one of the portions of random data.

.

65. (Previously Presented) A method of operating a computer to store a data set on a storage device, comprising:

determining a first location at a first offset within the storage device for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within

the storage device for storing the data set, said second offset determined using a process that is independent of a process used to generate said first offset: encrypting the data set;

writing the encrypted data set using a second storage writing process beginning at the second storage writing process starting location in a portion of random data; creating the file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location: encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location.

- 66. (Previously presented) The method according to claim 64 in which the determining the first storage writing process starting location for creating the file index comprises adding a predetermined offset to the first storage writing process starting location as a beginning of the file index.
- 67. (Previously presented) The method according to claim 64 wherein the encrypted file index is stored only within the portions of random data on the device.
- 68. (Previously Presented) The method according to claim 64 in which the encrypted file index is stored within one or more of the portions of random data by writing over random data portions within the storage device with the encrypted file index data.

Art Unit: 2166

 $\,$ 69. (Previously presented) The method according to claim 64 wherein the encrypted

data set is stored only within the portions of random data.

70. (Previously Presented) The method according to claim 64 in which the encrypted

data set is stored within one or more of the portions of random data by writing over

random data portions within the storage device with the encrypted data set.

71. (Previously presented) The method according to claim 64 which further comprises a

using the user input passphrase for generating a key for encrypting the file index.

72. (Previously presented) The method according to claim 64 in which the passphrase

is used for generating a key for encrypting the data set.

73. (Previously presented) The method according to claim 64 in which the passphrase

is used in selecting the second storage writing process starting location.

74. (Previously Presented) The method according to claim 64 in which at least one of

the first location within one of the portions of random data, the second location within

one of the portions of random data, a key for the file index and a key for the data set is

determined by using at least one hash function to operate on the user input passphrase.

Art Unit: 2166

75. (Previously Presented) The method according to claim 64 in which the passphrase is operated on once to produce an output which is used for determining at least two of the first location within one of the portions of random data, the second location within one of the portions of random data, a key for the file index and a key for the data set.

76. (Previously Presented) The method according to claim 64 in which the passphrase is operated on a plurality of times, each operation generating an output for use in determining at least one of the first location within one of the portions of random data, the second location within one of the portions of random data, a key for the file index and a key for the data set.

77. (Previously presented) The method according to claim 64 in which a common key is used for encrypting the data set and for encrypting the file index.

78. (Previously presented) The method according to claim 64 which comprises a step of storing further sets of data using said passphrase.

79. (Previously presented) The method according to claim 78 which is such that a respective location for each data set is selected, each data set is encrypted and stored at the respective location, and respective entries are added to the file index.

Art Unit: 2166

80. (Previously Presented) The method according to claim 64, comprising a step of storing further file indexes within one of the portions of random data, each of which is associated with a respective passphrase and each of which is encrypted and is stored at a location selected in dependence on the respective passphrase.

- 81. (Previously presented) The method according to claim 80 in which respective encryption keys are generated from the respective passphrases and these respective keys are used for encrypting data sets which are associated with each file index.
- 82. (Previously Presented) The method according to claim 80 comprising a step of selecting the passphrase for, and hence location for, an additional file index with knowledge of the respective passphrases corresponding to file indexes already stored in one of the portions of random data such that collisions may be avoided.
- 83. (Previously Presented) The method according to claim 80, in which, there are a plurality of file indexes stored in one of the portions of random data, the method comprises a step of selecting a location for an additional data set with knowledge of the respective passphrases corresponding to file indexes already stored in one of the portions of random data such that collisions may be avoided.
- 84. (Previously Presented) The method according to claim 80 comprising a step of storing additional data sets using an additional passphrase whilst in ignorance of at

Art Unit: 2166

least one other existing passphrase.

85. (Previously Presented) The method according to claim 80 comprising a step of storing data sets in a predetermined relationship to a respective file index to help prevent collisions, for example the data sets may be stored adjacent to the respective file index, the data sets may be stored substantially contiguously to the respective file index, and the data sets may be stored at locations close to but after the respective file index.

86. (Previously Presented) The method according to claim 64 comprising a step of storing data on the storage device carrying a plurality of files of random data.

87. (Previously presented) The method according to claim 64 in which the file index comprises a message authentication code.

88. (Previously presented) The method according to claim 87 in which the file index comprises a message authentication code of all associated data sets so as to facilitate detection of tampering.

89, (Previously Presented) The method according to claim 87 in which the file index comprises a message authentication code of one of the portions of random data in its

Art Unit: 2166

entirety for use in detecting other usage of one of the portions of random data.

90. (Previously presented) The method according to claim 64 comprising a step of pre

processing the data set prior to encryption.

91. (Previously Presented) The method according to claim 64 comprising a step of

presenting a user with an indication of a location within one of the portions of random

data that will be selected for the file index when using a predetermined passphrase,

92. (Previously Presented) The method according to claim 91 comprising a step of

accepting user entered trial passphrases and providing a user with an indication of a

location within one of the portions of random data that will be selected for the file index

for each trial passphrase.

93. (Previously Presented) The method according to claim 91 comprising a further step

of providing to the user an indication of the regions of one of the portions of random

data that are already occupied by file indexes having passphrases that have been

supplied by the user.

94. (Previously Presented) The method according to claim 64 comprising a step of

receiving an indication from a user of a location within one of the portions of random

data which the user desires to use for the file index

- 95. (Previously Presented) The method according to claim 94 further comprising a step of suggesting possible passphrases to the user in response to the user indicating a location within one of the portions of random data which the user desires to use for the file index.
- 96. (Previously presented) The method according to claim 94 comprising steps of receiving a user input passphrase and suggesting a modified passphrase.
- 97. (Previously presented) The method according to claim 96 in which the modification of the passphrase is selected so as to at least one of: move a location at which an associated index would be stored towards a desired location indicated by a user and strengthen the passphrase.
- 98. (Previously Presented) The method according to claim 64 comprising a step of deleting the data set stored on the storage device.
- 99. (Previously presented) The method according to claim 98 comprising a step of removing a respective entry from the file index.
- 100. (Previously Presented) The method according to claim 99 in which the step of deleting the data set comprises a step of overwriting the data set with random data as

Art Unit: 2166

well as removing the entry from the file index.

101. (Previously Presented) The method according to claim 98 comprising a step of reorganizing data stored in association with the file index when at least one data set referenced in that file index is deleted.

102. (Previously Presented) The method according to claim 100 in which the step of overwriting the data set comprises a step of using at least one random data and encrypted data stored in one of the portions of random data for generating pseudorandom data for overwriting deleted files.

103. (Previously Presented) The method according to claim 102 in which the method comprises a step of using random numbers from one of the portions of random data that would be overwritten when adding a further data set to replace any pseudo-random values previously used elsewhere within one of the portions of random data.

104. (Previously presented) A computer storage device for steganographically concealing stored information, said device configured with at least one storage area having one or more portions of random data containing a file index and a predetermined data set, and software carrying out steps wherein the file index is encrypted and is stored at a first location determined by an algorithmic process dependent upon a user passphrase, and the data set is encrypted and is stored at a second location

Art Unit: 2166

determined using a process that is unconstrained by the process used to determine the first location, and the file index comprises an information indicative of the second location.

105. (Previously presented) The storage device according to claim 104 further including application software stored thereon for execution by a computer to enable steganographic storage extraction of data sets in the one or more portions of random data.

106. (Previously presented) The storage device according to claim 104 in which the passphrase is used to generate a key for at least one of encrypting the file index and encrypting the data set.

107. (Currently amended) The storage device according to claim 104 further comprising a software application stored by the storage device, the software comprising instructions that when loaded and executed by a computer cause the computer to perform at least one of the following operations:

accepting a plurality of user input passphrases and generating corresponding encryption/decryption keys;

determining respective storage writing process starting locations for storage of a plurality of file indexes;

encrypting the plurality of file indexes;

Art Unit: 2166

encrypting a plurality of data sets;

storing the plurality of file indexes;

determining respective storage writing process starting locations for storing a plurality of data sets:

storing the plurality of data sets;

accepting one or more user input passphrases and using said one or more user input passphrases for locating and decrypting the respective file indexes;

locating one or more encrypted data sets stored within the storage device: decrypting the one or more encrypted data sets stored within the storage device; and outputting the one or more decrypted data sets stored within the storage device as an encrypted data set.

108, (Previously presented) The storage device according to claim 104 further including a conventional file allocation table stored thereon.

109, (Previously presented) The storage device according to claim 104 wherein at least a portion of the device comprises a Read Only Memory (ROM).

110. (Previously Presented) The storage device according to claim 108 further comma Read Only Memory (ROM) portion wherein is stored the file allocation table, the software and an operating system header file.

Page 14

111. (Previously presented) The storage device according to claim 104 wherein the device is operable as a removable storage device.

112. (Previously presented) The storage device according to claim 104 wherein the device is assigned a particular identifying serial number.

- 113. (Previously Presented) The storage device according to claim 104 further including a unique hard coded identifier data stored in memory contained therein said identifier data for use by a computer for at least one of:
- a) an encryption process used for encrypting at least one of the file index and the data set: and
- b) a decryption process used for decrypting at least one of the file index and the data set.
- 114. (Previously presented) The storage device according to claim 104 wherein the storage device has the appearance of a conventional portable memory storage device.
- 115, (Currently amended) A computer arranged configured under the-control of software computer executable program code, said computer executing software program code including instructions for configuring the computer to steganographically storing store a data set on a storage device within one or more portions of random data contained on said a digital data storage device coupled to said computer, comprising:

Art Unit: 2166

<u>first storage writing process</u> programmable logic circuitry configured to determine a first <u>starting</u> location within <u>a portion of random data on</u> the storage device for initiating a first storage writing process for storing a file index;

second storage writing process programmable logic circuitry configured to determine a second storage writing process starting location at a second offset within a portion of random data on the storage device for storing the data set where said storage writing process starting location is determined independently from the process used to select the first location;

<u>data set encryption</u> programmable logic circuitry configured to encrypt the data set;

<u>data set storing</u> programmable logic circuitry configured to write the <u>an</u> encrypted data set using the a the second storage writing process beginning at the second storage writing process starting location in a portion of random data;

file index programmable logic circuitry configured to create a file index including an entry in the file index in respect of the data set, the entry comprising an indication of a memory location within the storage device of the second storage writing process starting location:

file index encryption programmable logic circuitry configured to encrypt the file index; and file index storing programmable logic circuitry configured to write the an encrypted file index using the first storage writing process beginning at the first storage writing process-starting location in the portion of random data.

116. (Currently amended) The computer according to claim 115 further comprising file

Art Unit: 2166

index location indicating programmed logic circuitry configured by said software to provide a user with an <u>visual</u> indication of a location within a-the_portion of random data that will-determined by said first storage writing process programmable logic circuitry to be used for storing the file index corresponding to when a particular, passphrase is input by a user.

- 117. (Currently amended) The computer according to claim 115 which is arranged under the control of software to accept user entered trial passphrases and provide a user with an indication of a location within the file portion of random data that will be selected for storing the file index for each trial passphrase.
- 118. (Currently amended) The computer according to claim 115 which is arranged under the control of software-further comprising passphrase input processing programmed logic circuitryconfigured to provide a user an indication of regions of the portions of random data that are already occupied by file indexes having associated with passphrases that have been-supplied by a user.
- 119. (Currently amended) The computer according to claim 115 which is arranged under the control of software-further comprising passphrase input processing programmed logic circuitry configured to suggest possible passphrases to a user in response to a user indicating a location within the a portion of random data which a user

Art Unit: 2166

desires to use for storing the file index.

120. (Currently amended) The computer according to claim 116 which is arranged under the control of software-further comprising user interface programmed logic circuitry configured to present-provide a user interface for displaying the visual indications on a display device connected to the computer.

121, (Currently amended) The computer according to claim 120 in which the user interface is arranged programmed logic circuitry is configured so that a user can use a pointing device to indicate select a location within the a portion of random data which a user decires to use for storing a the file index.

122. (Currently amended) A method of extracting a data set steganographically stored on a storage device having one or more portions random data containing a file index and a predetermined data set, wherein the file index is encrypted and is stored at a first location determined by an algorithmic process dependent upon a user input passphrase, and the data set is encrypted and is stored at a second location determined using a process that is unconstrained by the process used to determine the first location, and the file index comprises information indicative of the second location, comprising:

using a user input passphrase to determine a location for a-the file index based upon

Art Unit: 2166

the user input passphrase;

decrypting the file index;

identifying a location of the data set from the decrypted file index; and decrypting the data set stored at the identified location.

123. (Previously presented) A computer arranged under the control of software to extract data using the method according to claim 122.

124. (Previously presented) A method of storing a data set on a storage device comprising:

determining a first location within the storage device for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within the storage device for storing the data set,. said second offset

determined using a process that is independent of a process used to generate said first location:

encrypting the data set;

writing the encrypted data set using a second storage writing process beginning at the second storage writing process starting location in a portion of random data; creating a file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location; encrypting the file index; and

Art Unit: 2166

writing the encrypted file index using the first storage writing process beginning at the first storage writing process starting location, the method further comprising, prior to a user finalizing a user input passphrase, accepting input of at least one user input trial passphrase and providing a user with an indication of a location within the portion of random data that will be determined for creating the file index associated with the at least one user input trial passphrase.

125. (Previously presented) A computer readable data storage medium, said storage medium storing a computer program comprising code portions which when executed a computer cause the computer to perform steps of:

determining a first location within the storage medium for initiating a first storage writing process for storing a file index;

determining a second storage writing process starting location at a second offset within the storage medium for storing a data set said second offset determined using a process that is independent of a process used to determine said first location; encrypting the data set;

writing the encrypted data set using a second storage writing process beginning at the second storage writing process starting location in a portion of random data; creating the file index including an entry in the file index in respect of the data set, the entry comprising an indication of the second storage writing process starting location; encrypting the file index; and

writing the encrypted file index using the first storage writing process beginning at the

Art Unit: 2166

first storage writing process starting location in the portion of random data.

126. (Currently amended) A method of storing a data set on a computer accessible digital data storage device having a data storage area that is initialized with comprising:

<u>initializing</u> one or more portions of random <u>a digital</u> data <u>storage area of the storage</u> <u>device with random data</u>; comprising the steps of

determining a first writing process starting location within a data storage portion initialized with random data for creating a file index:

determining a second writing process starting location within a data storage portion initialized with random data for storing the data set, said second writing process starting location determined using a process that is unconstrained by a process used to determine said first writing process starting location;

encrypting the data set;

storing the encrypted data set beginning at the second writing process starting location, using only data storage portions initialized with random data:

making an entry in the <u>creating a</u> file index indicative of which portions of the data storage device initialized with random data are to be used to store the <u>encrypted</u> data set, wherein an indication of the second writing process starting location is determinable from the file index:

encrypting the file index; and

Art Unit: 2166

storing the encrypted file index-at the first determined location in the data storage area initialized with random data beginning at the first writing process starting location..

127. (Currently amended) The method according to claim 126-wherein the step of ensuring that an indication of the second selected determined location is determinable from the file index comprises the step of further comprising:

making an entry in the file index in respect of the data set, the entry comprising an indication of the second writing process starting determined-location.

128. (Currently amended) The method according to claim 126 wherein the step of determining a first location within the data storage area initialized with random data for storing the file index, comprises

the step of determining-wherein the first writing process starting location from a plurality of predetermined possible locations within the data storage area initialized with random data, is determined in dependence upon one of: an input received from a user to a computer accessing the storage device; and a selection computing implemented determining process which is independent of user input.

129. (Currently amended) The method according to claim 126 wherein the step of determining a first location within the data storage area initialized with random data for storing a file, comprises steps of selecting the first writing process starting location in dependence is dependent upon a user input passphrase and associating the file index

Art Unit: 2166

is associated with the user input passphrase.

130. (Currently amended) The method according to claim 129 wherein said data set is stored under protection of said user input passphrase and the method comprising a further step of further comprising:

storing a second data set on the storage device under protection of wherein a writing process for storing the second data set is dependent upon a second user input passphrase, the etep-process of storing the second data set on the storage device comprising-steps-of:

selecting-determining, in dependence on the second user input passphrase, a third writing process starting location within a the data storage area-portion initialized with random data for storing creating a second file index;

selecting determining a fourth <u>writing process starting</u> location within the a data storage area <u>portion</u> initialized with random data for storing the second data set;

encrypting the second data set;

storing the encrypted second data set <u>beginning</u> at the fourth <u>selected writing process</u> <u>starting</u> location in the <u>a</u> data storage area initialized with random data;

ensuring that an indication of the fourth-selected location is determinable from the second file index-creating a file index indicative of which portion of the data storage device are used to store the encrypted second data set;

encrypting the second file index; and storing the encrypted second file index at the third selected location in the data-storage area initialized with random data, and comprising,

Art Unit: 2166

before the step of encrypting the second file index, a further step of recording in the second file index an indication of which parts of the data storage area initialized with random data will be used to store said second data setbeginning at the third writing process starting location.

- 131. (Currently amended) The method according to claim 126 wherein the one or more portions of the data storage area initialized with random data is are reserved only for use in storing data.
- 132. (Currently amended) The method according to claim 126 wherein one or more portions of the data storage area initialized with random data comprises a file of random data which that is managed by a conventional file system management process on a computer accessing the storage device.
- 133. (Currently amended) A removable digital data storage device comprising a for concealing stored information, said device having at least one data storage area initialized with containing random digital data, wherein and having a file index and a data set that are steganographically stored in the data storage area initialized with containing random digital data, and software carrying out steps wherein the file index is being encrypted and stored at a first location located at one or more first storage locations within the data storage area initialized with containing random digital data, the data set is being encrypted and stored at a second location-located at one or more

Application/Control Number: 10/588,657 Page 24

Art Unit: 2166

second storage locations within the data storage area initialized with containing random digital data where said one or more second storage locations are is-determined independently from the process used to determine the first storage location, the file index comprises an entry in respect of the data set, the entry comprising an indication of the second location within the data storage area initialized with random data, and the file index comprises an indication of including information for identifying said second storage locations and indicating which parts of the data storage area initialized with containing random digital data are in use-being used to store said data set.

134. (Currently amended) A removable digital data storage device earrying on which is stored a software application program and comprising a which includes at least one data storage area initialized with random data, the software application program comprising computer executable code portions which when leaded and run on executed by a computer cause the computer to execute a method of storing a data set on the storage device, the method comprising the steps of: selecting a first location within the data storage area initialized with determine one or more first storage locations within the random data to be used for storing a file index; selecting a second location within the data storage area initialized with determine one or more second storage locations within the random data to be used for storing the a data set, where said one or more second storage locations being is determined by a process which is not constrained by independently from the process used to select the first location:

Art Unit: 2166

encrypting the data set;

storing the store an encrypted data set at-the second selected location in the data storage area initialized with random data one or more of said second storage locations; ensuring that an indication of the second selected location is determinable from the file index:

encrypting the file index create a file index containing information for identifying saib one or more second storage locations within the random data and for indicating which parts of the data storage area initilized with random data are being used to store the data set; encrypt the file index; and

storing the store an encrypted file index at the first selected location in the data storage area initialized with random data, and comprising, before the step of encrypting the file index, a further step of recording in the file index an indication of which parts of the data storage area initialized with random data will be used to store said data set said one or more first storage locations.

135. (Previously presented) A method of storing a data set on a storage device having one or more portions of random data, comprising:

determining a first storage writing process starting location at a first offset within a portion of random data for initiating a first storage writing process for storing a data set; determining a second storage writing process starting location at a second offset within a portion of random data for initiating a second storage writing process that creates a file index,

Art Unit: 2166

said second offset determined independently from a process used to generate the first offset:

encrypting the data set;

writing the encrypted data set using said first storage writing process beginning at said first storage writing process starting location;

creating a file index having an entry in respect of the data set, the entry comprising at least an indication of the first storage writing process starting location;

encrypting the file index; and

writing the encrypted file index using said second storage writing process beginning at said second storage writing process starting location.

136. (Previously presented) The method of claim 135 wherein said second offset is determined using an algorithm that is dependent upon an input passphrase.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to BRUCE A. WITZENBURG whose telephone number is (571)270-1908. The examiner can normally be reached on M-F 9:00 - 6:00.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Hosain Alam can be reached on 571-272-3978. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2166

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Bruce A Witzenburg/ Examiner, Art Unit 2166

/Etienne P LeRoux/ Primary Examiner, Art Unit 2161